Measurement Time Method for Engine Assembly Line with Help of Maynard Operating Sequencing Technique (MOST)

Tarun Kumar Yadav

Department of Mechanical Engineering Singhania University, Rajasthan, India

Abstract-This paper presents TATA plant based Measurement time method for engine assembly line with help of Maynard operating sequencing technique (MOST). Knowledge Based Design Methodology (KBDM) for automated and manual assembly lines, which can be applied equally well to single, multi- and mixed-product assembly lines with either deterministic operation times or stochastic operation times. The methodology starts from a suitable assembly system selection and thereafter decides suitable cycle times, parallel workstation requirements, and parallel line implementation for the type of assembly system being selected. An economical number of workstations are decided with the aid of workstation combining options depending upon the factual information provided. The end result is the detailed design of a manufacturing assembly line. A case study from a practical assembly line is presented to illustrate how the KBDM works.

Keywords:-MOST, Standard Time, Most sheet, Delmia Process Engineer Software, Line balancing of engine process.

I. INTRODUCTION

Work measurement is a systematic procedure for the analysis of work and determination of time required performing key tasks in processes, it is typically based on time standards for manual tasks. The release of the Methods Time Measurement (MTM) system in the 1940s was an important step forward in predictive work measurement. It is defined as `a procedure which analyses any manual operation or method into the basic motions required to perform it.MTM assigns to each motion a predetermined time standard which is determined by the nature of the motion and the conditions under which it is made.

One of the major problems in applying MTM to manufacturing operations is that it is extremely tedious and time consuming, since a work analyst must observe and document each movement in great detail. In addition, such an approach generates large amounts of data which must be managed. The development and release of the MOST in the 1960s alleviated many of these problems, since it is much simpler and more efficient. It classifies all human movements into three basic categories, and the description of each category is done by assigning values to only a few standard parameters. It is the latest work measurement technique that can be easily implemented and practically maintained to not only estimate the standard time but also improve methods and maximize the resource utilization.

II. MOST ALGORITHMS

MOST is the latest work measurement technique that can be easily implemented and practically maintained to estimate the standard time and also improve methods which maximize the resource utilization. It was originally developed by H. B. Maynard & Company Inc. and has three versions Basic MOST for the activities between 20 sec to 2 min, Mini MOST for the activities shorter than 20 sec, and Maxi MOST for the activities above 2 min. MOST focuses on three types of object movements Such as General Move, Control Move, and Tool Use which are briefly explained hereunder

Establishing New Operation Time in Cylinder Hade assembly Preparation Area

Maynard Operating Sequencing Technique (MOST)

- 1. Important Component of MOST
- 2. Types of Sequence

1. Important Component of MOST

(a) Takt Time: Takt is a German word meaning "Conductors Baton". Takt time matches the pace of the manufacturing process to customer demand. Each manufacturing process works to the takt.

$$Takt = \frac{Total \ time \ available}{Total \ customer \ demand}$$

- (b) Work Standards: Types for measuring Work Standards
 - 1. Time Study
 - 2. Synthetic Time data
 - 3. MOST
- (c) Methods Time Measurement (MTM)
 - 1. Developed by H. B. Maynard, in 1948
 - 2. Based on micro motions established by the Gilbert
 - 3. Identifies the variables which affect the time to perform each motion

2. Types of Sequence Models

Sequence models represent the sequence of events that occurs when an object is moved or a tool is used. Predefined sequence models represent different types of activities.

General move phases: Sequence models are structured into phases used to describe the action performed. Each of the predefined sequence models has a different set of phases.

Parameters: Phases and sequence models are built using letters called parameters.

GET	PUT	RETURN
A B G	АВР	A

A = Action Distance

B = Body Motion

G = Gain Control

P = Placement

Time Calculation: To arrive at the time for the step:

- 1. Sum the index values = 6 + 6 + 1 + 6 + 0 + 1 + 0 = 20 (Refer data sheet page no. 53-56)
- 2. Multiply by a factor of 10 to get time value (in Basic MOST).

$$20 \times 10 = 200 \text{ TMU}$$

III. EXPERIMENT AND RESULT

Establishing New Operation Time in Cylinder Hade & Cylinder Block assembly Preparation Area

 $\label{thm:continuous} Table \mbox{-} 1$ MOST SHEET OUTPUT (CYLINDER HEAD ASSEMBLY FLOW)

Operation no.	Operation description	Most time	
		Sec	Min.
H10	Loading of head on Washing m/c	5.66	0.094333
H20	Washing of Head	54.72	0.912
H30	Cylinder Head Pulling & Pallet insertion	5.76	0.096
H40	Rotation of head by 180 deg	5.4	0.09
H50	Valve Insertion	4.68	0.078
H60	Rotation of head by 180 deg	5.4	0.09
H70	Camcap loosening	29.88	0.498
H80	Valve Guide Seal Pressing	21.24	0.354
H90	Valve Spring Assembly	18.36	0.306
H100	Lock half pressing	15.12	0.252
H110	Oscillation Checking	32.76	0.546
H120	Visual Inspection & History Filling	26.28	0.438
H130-Manual	Shim Selection-MANUALY	39.6	0.66
H130-Auto	Shim Selection	29.52	0.492
H140	Camcap Tightening	42.84	0.714
H150	Tappet Setting	52.2	0.87
H160	Front oil gallery plug fitment with anabond & teflon coating	11.88	0.198
H170	Oil Pressure Switch Fitment	13.32	0.222
H180	Exhaust stud fitment	27.36	0.456
H190	Oil Seal Fitment	11.52	0.192
H200	Thermostat Assembly Fitment	51.12	0.852
H210	Coolant Temperature sensor fitment	9.36	0.156
H220	Blow-by read valve fitment	16.56	0.276
H230	Rear Lifting hook fitment	16.56	0.276
H240	Rotation of head by 180 deg	5.4	0.09
H250	Spark Plug & HT Cable Fitment	16.92	0.282
H260	Front Lifting hook fitment	16.56	0.276
H270	Inlet stud fitment	27.36	0.456
H280	Visual Inspection, history card filling & placing head in trolley	27.36	0.456
	TOTAL TIME ALL HEAD LINE ASSEMBLY	640.7	10.67833

 $\label{eq:Table-2} \mbox{MOST SHEET OUTPUT (CYLINDER HEAD ASSEMBLY FLOW)}$

Operation no.	Operation description	Mos	t time
		sec	min
Manual station no.2	1)Manual turn over device for manual fitment of water by pass nipple (new design)	37.8	0.63
HL_OP010	pallet lifter/ Lowerer		0
HL_OP020	1)Cam Cap Loosening, 2)Oil Gallery Plug Fitment	47.88	0.798
HL_OP030	1)Spring seat positioning, 2)Valve guide seal pressing	38.88	0.648
HL_OP050	1)Automatic TOD for Manual Valve Inseration		0
HL_OP070	1)Repair in Station: 2)Spring Inseration, Lock Half Retainer Placement	42.12	0.702
HL_OP080	Semi-automatic Lock half press	58	0.9667
HL_OP100	Valve oscillation	58	0.9667
HL_OP120	Camera Check for Lock half assembly verification (Common for Both Petrol and Diesel Head)		0
HL_OP130	Valve Seat Area Leak Test		0
HL_OP150	1)Repair Out Station- 2)Thermostat cover fitment		0
HL_OP160 & 170	Shim selection Machine (Length: 1.5 Meter)	50.04	0.834
			0
HL_OP200	1)Cam cap Tightening, 2)Dummy Oil Pressure switch fitment	48.96	0.816
HL_OP210	Tappet clearance checking	0	0
HL_OP220	1)Oil Seal Fitment, 2)Rear Hook Fitment	37.08	0.618
HL_OP230	1)Coolant Temperature sensor Fitment, 2)Inlet stud Fitment	47.88	0.798
HL_OP250	1)Horizontal Turn table 2)Exhaust stud fitment 3)Front Hook fitment	44.64	0.744
HL_OP270	Pallet Lifter/ Lowerer		0
	TOTAL TIME OF ALL STATION	511.28	8.5213

Table -3

MOST SHEET OUTPUT (CYLINDER HEAD ASSEMBLY FLOW)

Operation no.	Operation no. Operation description		Most time	
		sec	min	
HAS OP 01	1)Positioning of Cylinder Head on Pallet,2)Loosening of camcaps	49.68	0.828	
HAS OP 02	1)Spring Seat Positioning, 2) Valve guide seal pressing	38.88	0.648	
HAS OP 03	1)Valve Insertion, 2)oil gallery plug fitment, 3)spring insertion, 4)Retainer placement	45	0.75	
HAS AUTO	1)Lockhalf pressing, 2)Camera Check for Lock half fitment, 3)Valve oscillation, 4)Leak testing of valve train	0	0	
HAS OP 04	Shim Selection Station 1: Gauging of Components	45.72	0.762	
HAS OP 05	Shim Selection Station 2: Positioning of Components	48.24	0.804	
HAS OP 06	1)Camcap Tightening, 2)Dummy Oil Pressure Switch fitment	48.6	0.81	
HAS OP 07	Tappet Clearance Checking	0	0	
HAS OP 08	1)Oil Seal fitment, 2)Thermostat fitment, 3)Rear Hook fitment	47.88	0.798	
HAS OP 09	1)Coolant Temperature Sensor Fitment, 2)Inlet Stud Fitment	47.16	0.786	
HAS TTT AUTO	Camshaft TTT IPV	0	0	
HAS OP 10	1)Rotation of Head by 180 deg, 2)Exhaust Stud fitment, 3)Front Lifting Hook fitment	54.36	0.906	
	TOTAL TIME ALL HEAD LINE ASSEMBLY	425.52	7.092	

IV. CONCLUSION

We will obtain below out come after completed Cylinder head assembly flow with the help of Myrdal Operating Sequencing Techniques (MOST). Time of the whole cylinder head assembly flow is below the 425.52 sec and the some station time above the 425.52 sec and also reduces work station and area of work station with man power.

Table -4

MOST OUTPUT COMPARISION SHEET					
MOST SHEET NUMBER	NO. OF WORK STATION	DESCRIPTION	TOTAL STATION TIME		OUTPUT DESCRIPTION
			SEC.	MIN.	
MOST 1	28	CYLINDER HEAD ASSEMBLY FLOW	640.7	10.678	
MOST 2	18	CYLINDER HEAD ASSEMBLY FLOW	511.28	8.521	REDUCE WORK STATION AND AREA OF WORK STATION WITH MAN POWER AND TIME
MOST 3	12	CYLINDER HEAD ASSEMBLY FLOW	425.52	7.092	REEDUCE TIME

REFERENCES

- [1] Maynard [1] Maynard's Industrial engineering hand books, Maynard Operating Sequencing Techniques for Assembly line balancing.[17.62-17.64]
- [2] Ill, Introduction to work study, In this book to study of Process Planning and Layout of plant.[4] [201-216]
- [3] Bard, J. F. (1989). Assembly line balancing with parallel workstations and dead time. International Journal of Production Research, 27 (6), 1005-1018.
- [4] Wild, R. (1975). Work organization, a study of manual work and mass production, New York: Wiley.
- [5] Womack, J., Jones, D., and Roos, D. (1990). The Machine that changed the world. Rawson Associates, New York. [4] Garg, S., Vrat, P., and Kanda, A. (1994). Work Culture in JIT environment. Productivity, 35(4):463–466.
- [6] Pilkington, A. (1998). Manufacturing strategy regained evidence for the best practice. California Management Review, 41:31–42. [6] Sanidas, E. (2000). The successful imitation of the Japanese lean production system by American firms: Impact on American growth. In ESRC Center for Business Research.
- [7] Oliver, N., Delbridge, R., and Barton, H. (2002).Lean production and Manufacturing performance improvement in Japan, the UK and US 1994-2001.Business Research. ESRC Centre for Business research. www.netec.mcc.ac.uk/ WoPEc/data/Papers. [8] Moen, O. (1999).The relationship between firm size, competitive advantages and export performance revisited. International Small Business Journal, 18:53–72. [9] UMAS Engineering consultant firm ebookbrowse.com